




HACKET MASTER LINK ASSEMBLY – LOAD CAPACITY TABLE

Master Links


Certified to :-
DNV 2.7-1 & EN 1677-4



Part Code	Part Number	S.W.L. 0-45°(t)	Dimensions (mm)			Safety Factor	Mass (kg)
			A	B	C		
330.160	HA-16 ML	3.6	16	120	61	8.0	0.57
330.22S	HA-22 MS	6.8	22	162	90	7.8	1.63
330.220	HA-22 ML	4.5	22	270	140	8.0	2.30
330.28S	HA-28 MS	11.2	28	200	110	6.6	2.97
330.280	HA-28 ML	8.8	28	270	140	7.2	3.81
330.320	HA-32 ML	13.1	32	270	140	6.2	5.05
330.360	HA-36 ML	18.3	36	270	140	5.4	6.50
330.400	HA-40 ML	23.0	40	280	155	5.1	8.51
330.450	HA-45 ML	29.0	45	320	175	5.0	12.25
330.460	HA-46 ML	19.5	45	490	265	5.3	17.80
330.500	HA-50 ML	36.0	50	350	195	5.0	16.64
330.580	HA-58 ML	48.0	58	410	220	5.0	26.00
330.700	HA-70 ML	70.0	70	490	265	5.0	45.39
330.900	HA-90 ML	110	90	500	300	5.0	88.00

Quad Assemblies

Certified to :-
DNV 2.7-1 & EN
1677-4



Part Code	Part Number	S.W.L. 0-45° (t)	Dimensions (mm)						Safety Factor	Mass (kg)
			A	B	C	D	E	F		
350.160	HA-16 QA	3.6	16	120	61	14	120	60	8.0	1.42
350.220	HA-22 QA	6.8	22	162	90	20	140	70	7.8	3.67
350.230	HA-23 QA	4.5	22	270	140	16	120	61	8.0	3.66
350.260	HA-26 QA	8.8	28	270	140	20	140	70	7.2	5.89
350.280	HA-28 QA	11.5	28	200	110	22	140	70	6.5	6.22
350.320	HA-32 QA	13.1	32	270	140	26	185	90	6.2	9.77
350.360	HA-36 QA	18.3	36	270	140	28	185	90	5.4	11.92
350.400	HA-40 QA	23.0	40	280	155	32	200	110	5.1	16.41
350.450	HA-45 QA	29.0	45	320	175	36	225	125	5.0	23.53
350.460	HA-46 QA	19.5	45	490	265	30	185	90	5.3	25.10
350.500	HA-50 QA	36.0	50	350	195	40	260	130	5.0	32.31
350.580	HA-58 QA	48.0	58	410	220	50	350	195	5.0	59.28
350.700	HA-70 QA	70.0	70	490	265	58	410	220	5.0	97.38
350.900	HA-90 QA	110	90	500	300	70	420	240	5.0	160